



GJ7-12L/C • GJ7-22L/C*



GJ5-12LM
GJ7-12LM/C • GJ7-22LM/C



GJ10-12L/A* • GJ10-22L/A
GJ10-22R/A* • GJ12-22L/A*



GJ10-12LM/A* • GJ10-22LM/B
GJ10-22RM/A • GJ12-22LM/A*



GJ18-22LM/C • GJ21-22LM/C

Modelo	Capacidade Refrig. (Btu/h)	Capacidade Aquec. (W)	Ph-V-Hz	Pot. Elét. Refrig. / Aquec. (W)	Nível int. de Ruído dB (A)	Dimensões		
						Larg. (mm)	Alt. (mm)	Prof. (Mm)
GJ5-12LM	5600		1-127-60	560/ -	55	470	335	378
GJ7-12LM/C	7000		1-127-60	700/ -	55	470	335	390
GJ7-22LM/C	7000		1-220-60	700/ -	55	470	335	390
GJ7-12L/C	7500		1-127-60	755/ -	55	470	335	450
GJ7-22L/C	7000		1-220-60	710/ -	55	470	335	450
GJ10-12L/A	10100		1-127-60	980/ -	51	560	375	600
GJ10-12LM/A	10100		1-127-60	980/ -	51	560	375	600
GJ10-22L/A	10100		1-220-60	980/ -	52	560	375	600
GJ10-22LM/B	10500		1-220-60	1010/ -	48	560	375	600
GJ10-22R/A	10100	3100	1-220-60	980/ 3100	52	560	375	600
GJ10-22RM/A	10100	3100	1-220-60	980/ 3100	52	560	375	600
GJ12-22L/A	12000		1-220-60	1230/ -	53	560	375	600
GJ12-22LM/A	12000		1-220-60	1230/ -	48	560	375	600
GJ18-22LM/C	18000		1-220-60	1830/ -	54	660	428	700
GJ21-22LM/C	21000		1-220-60	2180/ -	56	660	428	770