

Modelo	Capacidade Refrig./Aquec. (Btu/h)	Ph-V-Hz	Pot. Elét. Refrig./Aquec. (W)	Nível int./ext. de ruído db (A)	Dimensões Unidade Interna / Externa		
					Larg. (mm)	Alt. (mm)	Prof. (mm)
GST 24-22L/E	24.000/ -	1-220-60	2800/ -	49/59	1300/950	195/840	600/412
GST 24-22R/E	24.000/24.000	1-220-60	2800/2800	49/59	1300/950	195/840	600/412
GST 36-22L/A	36.000/ -	3-220-60	4200/ -	49/62	1590/950	238/850	695/410
GST 36 22 R/A	36.000 / 37.000	3-220-60	4200/3800	49/62	1590/950	238/850	695/410
GST 36-38 L/A	36.000/ -	3-380-60	4350/ -	49/62	1590/950	238/850	695/410
GST 36-38 R/A	36.000 / 37.000	3-380-60	4350/3900	49/62	1590/950	238/850	695/410
GST 42-22L/A	42.000/ -	3-220-60	5100/ -	55/64	1590/950	238/1250	695/410
GST 42-22R/A	42.000/42.000	3-220-60	5100/5050	55/64	1590/950	238/1250	695/410
GST 42-38L/A	42.000/ -	3-380-60	5050/ -	55/64	1590/950	238/1250	695/410
GST 42-38R/A	42.000/42.000	3-380-60	5050/5000	55/64	1590/950	238/1250	695/410
GST 60-22L/A	60.000/ -	3-220-60	6650/ -	58/65	1590/950	238/1250	695/410
GST 60-22R/A	60.000/60.000	3-220-60	6650/6050	58/65	1590/950	238/1250	695/410
GST 60-38L/A	60.000/ -	3-380-60	6650/ -	58/65	1590/950	238/1250	695/410
GST 60-38R/A	60.000/60.000	3-380-60	6650/6050	58/65	1590/950	238/1250	695/410
GST80-38L/A	80.000/ -	3-380-60	9500/ -	58/68	2300/990	330/1700	780/840